



[Applications](#)

[About the System](#)

[Accu-Tab System Team](#)

[Resources](#)

[Contact Us](#)

[Chlorinators](#)

[Resources](#)

[Accu-Tab System](#)

[Competitive Comparison](#)

[FAQs](#)

# A Chlorinator for Every Pool, a Pool for Every Chlorinator



Whatever the size of your aquatic facility, the Accu-Tab® Water Treatment system can easily integrate into your existing operation. With three chlorinator series to choose from, each *Accu-Tab* chlorinator is solidly built in the USA using high-quality PVC that is both durable and corrosion resistant.

Select the option below that's right for you:

[Plug and Play Automation](#)

[Gravity or Side Suction](#)

[Hotel/Motel/Apartment Complex \(HMAC\)](#)



## Plug and Play Automation

### Accu-Tab PowerBase® Series Chlorination Systems

*The Accu-Tab PowerBase® chlorinator from Axiall is a true plug-and-play system that's easy to install and operate. There are four models to choose from depending on the size of your pool. These units have been designed to work with your automatic*



[About the System](#)

[Accu-Tab System Team](#)



- Indoor pools up to 360,000 gallons
- Automated Pressure side feed
- 2.8 lbs per hour maximum delivery
- 30-lbs (13.6 KG) tablet capacity
- 29"W x 25"L x 40"H

**MODEL SPECIFICATIONS**



- Indoor pools up to 1,120,000 gallons
- Automated Pressure side feed
- 10.2 lbs per hour maximum delivery
- 70-lbs (31.8 KG) tablet capacity
- 22"W x 34"L x 52"H

**MODEL SPECIFICATIONS**



- Indoor pools up to 2,000,000 gallons
- Automated Pressure side feed
- 22 lbs per hour maximum delivery
- 140-lbs (63.4 KG) tablet capacity
- 25"W x 45"L x 51"H

**MODEL SPECIFICATIONS**



**POWERBASE 3500**



- Indoor pools up to 4,800,000 gallons
- Automated Pressure side feed
- 36.4 lbs per hour maximum delivery
- 500-lbs (227 KG) tablet capacity
- 31"W x 63"L x 52"H

**MODEL SPECIFICATIONS**

**Gravity or Side Suction**

**Accu-Tab 3000 Series Chlorination Systems**



[Applications](#)

[About the System](#)

[Accu-Tab System Team](#)

[Resources](#)

[Contact Us](#)



- Indoor pools up to 200,000 gallons
- Gravity or Suction side feed
- Up to 0.57 lb per hour maximum delivery
- 12-lbs (5.4 KG) tablet capacity
- 26"H x 9" dia

**[DELIVERY CURVE](#)**



- Indoor pools up to 1,120,000 gallons
- Gravity or Suction side feed
- 10.2 lbs per hour maximum delivery
- 75-lbs (34 KG) tablet capacity
- 26"H x 9" dia

**[DELIVERY CURVE](#)**

**SERIES 3500**



- Indoor pools up to 2,000,000 gallons
- Gravity or Suction side feed
- 22 lbs per hour maximum delivery
- 150-lbs (75 KG) tablet capacity
- 26"H x 18" dia

**[DELIVERY CURVE](#)**



- Indoor pools up to 4,800,000 gallons
- Gravity or Suction side feed
- 36.4 lbs per hour maximum delivery
- 500-lbs (9227 KG) tablet capacity
- 27"H x 30" dia

**[DELIVERY CURVE](#)**


[Applications](#)
[About the System](#)
[Accu-Tab System Team](#)

[Resources](#)
[Contact Us](#)

## 100 SERIES CHLORINATOR SPECIFICATIONS



- Indoor pools up to 80,000 gallons
- Gravity or Suction side feed
- 0.8 lb per hour maximum delivery
- 8-lbs (3.6 KG) tablet capacity
- 21.3:H x 9" dia

### [MODEL SPECIFICATIONS](#)

## SERIES 3012



- Indoor pools up to 200,000 gallons
- Gravity or Suction side feed
- 1 lb per hour maximum delivery
- 12-lbs (5.4 KG) tablet capacity
- 26"H x 9" dia

### [MODEL SPECIFICATIONS](#)

## POWERBASE 1030



- Indoor pools up to 360,000 gallons
- Automated Pressure side feed
- 2.8 lbs per hour maximum delivery
- 30-lbs (13.6 KG) tablet capacity
- 29"W x 25"L x 40"H



### [MODEL SPECIFICATIONS](#)

## Restore Balance

### The Acid-Rite® pH Adjustment System

*An ideal replacement for messy muriatic acid, awkward handling of granular sodium bisulfate, and the high cost and inability to control alkalinity of CO2 systems. Aside from consistent deliver of acid, this automated tablet-based system requires very little maintenance.*



Applications

About the System

Accu-Tab System Team

Resources

Contact Us



[LEARN MORE](#)

**Applications**

- Aquatics and Fountains
- Food Safety & Irrigation Applications
- Municipal/Potable Water & Wastewater
- Industrial Water
- Aerobic and Onsite Water

**About the System**

- Proprietary Tech/Engineering
- Tablets
- Applications
- Chlorinator Models
- Competitive Comparison Tool
- Watch the Demo

**Accu-Tab System Team**

- Become a Specialist

**Resources**

- SDS
- Literature
- Tech Time with Tom
- Warranty
- Certifications
- Blog

**Contact Us**



Axiall Corporation, *A Westlake Company* | Headquarters: 11 Stanwix Street Suite 1470 Pittsburgh, PA 15222 | ©2020 Axiall Corporation • All Rights Reserved

The information presented in this website is for general informational purposes only. All sales of products by the subsidiaries or affiliates of Westlake Chemical Corporation are subject to the respective entity's standard terms and conditions of sale, which are available upon request. No warranty, express or implied, including, but not limited to, any warranty of merchantability or fitness for particular purpose, is made by this brochure, and any and all warranties on such products are limited to those expressly set forth in the applicable entity's standard terms and conditions. Further, any reliance the user places on the information contained in this brochure is strictly at the user's own risk.